Product Overview

MemoSolid

It's high-end Industrial & Military Secure SSDs Provider and Manufacturer.

Spica-S

MemoSolid Spica-S is 2.5 inch PATA military-grade Solid State Disk with SLC Nand Flash. Spica-S supports integral power fail protection feature, which is very important for some high-end industrial & military applications. Spica-S can support all kinds of military secure erase protocols, such as NSA130-2, NSA 9-12, IRIG, AR380-19, DoD 5220.22-M NISPOM, NAVSO P-5239-26, AFSSI-5020...etc.

Applications

MemoSolid military grade rugged Spica-S SSDs are designed to meet the needs of mission-critical applications in the defense, aerospace, industrial and embedded markets where high shock, vibration and High-low temperature tolerances are as important as high Read &Write performance and long-term reliability. The MemoSolid Military-grade rugged Spica-S drive also support all kinds of military secure erase protocols, such as NSA130-2, NSA 9-12, IRIG, AR380-19, DoD 5220.22-M NISPOM, NAVSO P-5239-26, AFSSI-5020...etc.

Integral Power Fail protection

A high-reliability power back-up system protects against data loss and corruption in the event of unexpected power interruptions. Spica-S series is designed with a 3F industrial-grade Capacitor, which supports Integral Power Fail Protection under extreme environments. It supports at least 3 Seconds of power supply, so as to ensure that all systems and user data will be written back to the NAND from DDR. The super capacitor inside Spica-S drive will never occur liquid leaking accident, which is very dangerous in military devices.

Features

- AES 256 Encryption
- Rugged and conformal coating
- Integral power fail protection
- Military protocols Secure Erase (Optional)

Spica SLC SSD Family

Model Name	Available Capacity	Performance
Spica-S	30/60/120/240/480GB	100/100 MB/s
Spica-S-FE	30/60/120/240/480GB	100/100 MB/s

Spica-S PATA Specifications

2.5-inch PATA 44 pins SLC Military Grade SSD	
Performance	
Access time	0.1 ms
Sustained Read/Write	100/ 100 MB/s
Random IOPS Read/Write	5500/ 13000
Capacity	
SLC	30, 60, 120, 240, 480GB
Reliability	
MTBF	> 2 000 000 hours, Telcordia 25°C
Data Reliability	< 1 non-recoverable error in 10^{14} bits read
Data Retention	> 10 years at 25°C
Warranty	3 Years
Power	
Input Voltage	5 V +/-5%
Idle (typ)	0.5 W
Operational (typ)	2.5W
Environmental	
Operating Shock	1500G peak, 0.5ms, Half sine
Vibration	20G peak, 20Hz to 2000Hz, Sine
Altitude	24,384 m [80,000 ft.]
Relative Humidity[3]	5% to 95% non-condensing
Conformal Coating	Yes
Operating Temp	Industrial -40°C to +85°C
Storage Temp	-55°C to 95°C
Mechanical	
Length	100 mm
Width	70 mm
Height	9.4 mm

Spica SLC SSD Ordering Information

Model number	Capacity (GB)	Remark
Spica-S30	30	Standard without secure erase function
Spica-S60	60	Standard without secure erase function
Spica-S120	120	Standard without secure erase function
Spica-S240	240	Standard without secure erase function
Spica-S480	480	Standard without secure erase function
Spica-S30-FE	30	Product with secure erase function
Spica-S60-FE	60	Product with secure erase function
Spica-S120-FE	120	Product with secure erase function
Spica-S240-FE	240	Product with secure erase function
Spica-S480-FE	480	Product with secure erase function

Spica-S Military protocols Secure Erase Specifications

ATA Command	Protocol Name	Description
F4h-0000	Fast erase	Erase all blocks, overwrite all locations with 0xFF
F4h-0001	DoD 5220.22-M NISPOM 8-306	Erase all blocks then overwrite all addressable locations with a single character “0x53”, then perform erase of all blocks
F4h-0010	DoD 5220.22-M NISPOM Supplement1	Erase all blocks, overwrite with “0x53”, Erase all blocks, and then overwrite with “0xAC”. Erase, overwrite with a pseudo-random character
F4h-0100	NSA130-2	Erase all blocks and overwrite all locations with a pseudo-random pattern two times, erase all blocks and overwrite with a pattern “0xAA”.
F4h-0110	AR380-19	Erase all blocks; overwrite all locations with a pseudo-random character. Erase all blocks, overwrite with “0x65”, erase all blocks, and overwrite with 0x9A.
F4h-1000	NAVSO P-5239-26	Erase all blocks; overwrite all locations with a random pattern. Wait 2 minutes, erase all blocks, program all locations with another random pattern, and verify 100%.
F4h-1010	AFSSI-5020	Erase all blocks, verify then overwrite with “0x55” pattern.
F4h-1011	NSA 9-12	Erase all blocks, overwrite all locations with a pattern 0xAA and verify 0.1% of randomly chosen locations
F4h-1100	IRIG	Erase all blocks; overwrite all locations with a pattern 0x55. Erase all blocks, and then overwrite with 0xAA. Erase all blocks.

MemoSolid Technology Limited

Address :

9th Floor, 2nd Building, YuanWangGu RFID Industrial Park, TongGuan Road, GuangMing District, Shenzhen 518107, China

Phone :

+86 (755) 2942 5519

Email :

Sales@memosolid.com support@memosolid.com

MemoSolid

www.memosolid.com

All parts of MemoSolid documentation are protected by copyright law and all rights are reserved. This documentation may not, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable from without prior consent, in writing, from MemoSolid Technology.