

TBOX-3601

Industrial Intel Skylake Celeron 3855U fan-less Box PC

Specification

V2.0

Brief Introduction

TAICENN TBOX-3601 is a high-performance fan-less industrial Box PC model, specially designed for machine vision, industrial network applications. It can adapt Intel Skylake Celeron-3855U CPUs, having advanced computer performance and low power consumption. TBOX-3601 storage can support 1 *mSATA SSD or HDD; The design has a variety of communication interface, with 5* LAN ports (4*Support PoE), 4* USB 3.0 port, 2* RS232 (Optional with 1* RS485), 8*GPIO; The power input is DC 9~36V voltage, and has over-current, over-voltage and reverse-polarity protection.

TAICENN TBOX-3601 uses full-sealed box construction, and it can prevent dust from entering the device system. Large aluminum fin heat sink can distribute the heat effectively and quickly, ensures the longer reliability and life-span of the system. TAICENN TBOX-3601 operating temp. is -20°C~+70°C, can be suitable for longer-time operating and harsh environment industrial application projects, such as intelligent transportation system, machine vision, medical device, textile machinery, rail transportation and industry automation. TAICENN TBOX-3601 can be compatible with Windows 7, Windows 7 Embedded, Windows8, Windows10, Linux Operating system and embedded Operating system, and it is also compatible with application software based on those operating systems.

Product Image




Specification parameter

Product model	TBOX-3601
System & Hardware	
BIOS	SPI AMI EFI BIOS
CPU	Celeron 3855U
CPU GHz	Dual-core 1.6Ghz
Memory	SO-DIMM, DDR4L, Max. up to 16GB
Storage	1* mSATA
GPU	Intel HD Graphics 510
Network	5* Intel I211AT (Optional Wifi/3G/4G)
Audio	Realtek ACL 269 Audio controller
Expansion	1x full-size mPCIe slot
Watch dog	0~255 seconds programmable
System	Windows 7, Windows 7 Embedded, Windows8, Windows10, Linux
I/O	
COM	COM1: RS232 COM2: RS232/RS485
Network	LAN1~LAN4 support PoE, 802.3AF standard (Single port Max. up to 15.4w) PoE total power less than 45W LAN5: RJ45
Audio	Line-In, Line-Out
USB	4* Camera USB3.0
Display	1*VGA, 1*HDMI
Power Input	DC 5.5*2.5
SIM	Sim slot
GPIO	8 channels Photoelectric isolated
Structure	
Box Structure and surface	Aluminum alloy, anodizing and anti-scratch treatment
Cooling System	Finned aluminum heatsinks
Color	Black
Indicator	Power Switch/ Power LED/ HDD LED
Mounting	Support Desktop, Wall-mounted,
Dimension	180 x 125 x 35 (mm)
Net weight	About 2.5KG

Power & Environmental	
Voltage Input	DC 9~36V (Over-current, Over-voltage and reverse polarity protection)
Power Consumption	25W (Max. 60w)
EMC	CE/FCC Class A
Working temperature	-20℃~+70 ℃
Storage temperature	-40℃~+80 ℃
Relative humidity	10~95%@10℃ (No condensation)
Vibration	50~500Hz,1.5G,0.15mm peak to peak
Shock	10G/peak (11ms sec)

Interface and Dimension



Ordering Information

TBOX-3601	Intel Celeron 3855U/1*HDMI/1*VGA/5*RJ45/4*USB/2*RS232/DC 9~36V/Line In/Line-Out
Memory	DDR4L 4G/8G/16G
Storage	SSD: 16GB/32GB/64GB/128GB/256GB/512GB/1TB HDD: 500GB/1TB
Wireless module	Wifi: 802.11b/g/n Mini PCIe 150M 3G/4G: All network 4G module

TAICENN Technology

*TAICENN, is a leading global **solution provider** of Embedded Box IPC, Touch panel IPC and industrial monitor, which are designed specifically for systems and applications that require excellent performance, high-level reliability and stability, long supply period and supports.*

The information in this specification is subject to change without notice

All parts of TAICENN Technology documentation are protected by copyright law and all rights are reserved. This documentation may not, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable form without prior consent, in writing, from TAICENN Technology.